

### 1. [Preparation](#) ;

Remove all items from the room to be painted. Remove any loose paint, dirt, grease, and other contaminants. Repair any damaged areas.

Remove any old paint, paper, or wallpaper. Refinishing, sanding, priming, drywall, etc. are all part of the preparation process.

[Priming](#) is an important step in the preparation process. It helps to seal the surface and provides a uniform base for the paint.

Remove any old paint or paper. This is a labor-intensive process, but it is necessary for a good finish.

Remove any old paint or paper. This is a labor-intensive process, but it is necessary for a good finish. **amp** is a common mistake. It is important to use the correct amount of paint.

Remove any old paint or paper. This is a labor-intensive process, but it is necessary for a good finish.

[Swiveling](#) is a common mistake. It is important to use the correct amount of paint.

### 2. [Specifications](#) Table

Power	220-240V, 50/60 Hz
Weight	1000 lbs
Dimensions	38 in
Capacity	40 gal / min
<a href="#">Flow rate</a>	13 gpm
Pressure	3.0 psi

### 3. [Accessories](#)

1.8 gal of 48M paint is required.

2 gal of primer is required.

[Primer](#) is required.

Remove any old paint or paper.

Remove any old paint or paper.

### 4. [Notes](#)

Remove any old paint or paper. This is a labor-intensive process, but it is necessary for a good finish.

# Production Process

Injection Moulding Machine



Assembly Line



Parts of Testing Equipments



Raw Material Warehouse &  
Finished Product Warehouse



# Our Team

## Activity, Cooperation, Home



Welcome to  
contact US!

