

## 1. Specificatie

|                                      |            |                                   |
|--------------------------------------|------------|-----------------------------------|
| Max Vermogen (W)                     |            | 1400 (0, -15%)                    |
| Gemiddeld Vermogen (W)               |            | 1200 (0, -15%)                    |
| Max.Suction Vermogen (W)             |            | ≥ 220                             |
| Max.Suction Efficiency (%)           |            | ≥ 18                              |
| Plug Type & amp; Schakelaar          |            | 250V-16A VDE, 250V-16 (8) A, T125 |
| Netsnoer Specification & amp; Lengte |            | 2 * 1mm² VDE 0.75mm               |
| Power Control Type                   |            | Vast                              |
| Gebruik Type                         |            | Nat en droog                      |
| Reinigen Efficiency (%)              | Tapijt     | ≥ 65%                             |
|                                      | Hard Floor | ≥ 95%                             |
| Diameter van Accessory               |            | Φ32                               |

## 2. Accessoires & Onderdelen Informatie

Pijp: Roestvrij Telescoop Pipe;

Kwast: Metal Brush, Water Brush;

Nozzle: 2 Kleine Nozzle

## 3. Verpakking Informatie

|                        |                 |
|------------------------|-----------------|
| Unit Dimension (mm)    | 385 * 420 * 630 |
| Pakket Afmetingen (mm) | 450 * 405 * 625 |
| Netto Gewicht (KG)     | 5.6 ± 0.2       |
| Bruto Gewicht (KG)     | 9 ± 0,2         |
| Capaciteit 40'HC (PCS) | 580             |

