

## 1. Specificatie

Max Vermogen (W)	1400 (0, -15%)	
Gemiddeld Vermogen (W)	1200 (0, -15%)	
Max.Suction Vermogen (W)	≥ 220	
Max.Suction Efficiency (%)	≥ 18	
Plug Type & amp; Schakelaar	250V-16A VDE, 250V-16 (8) A, T125	
Netsnoer Specification & amp; Lengte	2 * 1mm <sup>2</sup> VDE 0.75mm	
Power Control Type	Vast	
Gebruik Type	Nat en droog	
Reinigen Efficiency (%)	Tapijt	≥ 65%
	Hard Floor	≥ 95%
Diameter van Accessory	Φ32	

## 2. Accessoires & amp; Onderdelen Informatie

Pijp: Roestvrij Telescoop Pipe;

Kwast: Metal Brush, Water Brush;

Nozzle: 2 Kleine Nozzle

## 3. Verpakking Informatie

Unit Dimension (mm)	385 * 420 * 630
Pakket Afmetingen (mm)	450 * 405 * 690
Netto Gewicht (KG)	5.8 ± 0.2
Bruto Gewicht (KG)	10 ± 0,2
Capaciteit 40'HC (PCS)	530

# Production Process

Injection Moulding Machine



Assembly Line



Parts of Testing Equipments



Raw Material Warehouse & Finished Product Warehouse

# Our Team

## Activity, Cooperation, Home



Welcome to  
contact US!

